

RAY 2000 C/I



Part number	04003094
Lampholder:	cabla
Light Source:	HALOGEN METAL HALIDE LAMPS (HIE)
Wattage:	1x2000 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 2.6J xx5
Optic:	INTENSIVE CIRCLE REFLECTOR
Optic Beam:	15°
Ta MIN luminaire:	-30°
Ta MAX luminaire:	35°




Description


Metal halide floodlight for indoor and outdoor lighting, comprising:

- Die-cast painted aluminium housing and trim
- Flat tempered glass diffuser
- Extra pure polished aluminium reflectors
- Anti-aging silicone gasket
- Electrical wiring box with ignitor, supplied with the luminaire, made of technopolymer reinforced with glass fibre
- Automatic line isolator switch in LCP
- Internal wiring in nickel-plated copper with THT silicone insulation
- Ceramic lamp supports with stainless steel check spring
- Stainless steel external screws
- Fully integrated stainless steel safety spring clips
- Painted steel bracket
- Patented anti-vacuum device
- Graduated goniometer for aiming purposes
- Retractable stainless steel aiming device
- Adequate power supply units, available as accessories, must be used for all floodlights

Photometric data



Technical drawings



CONTROL GEAR

RAY 2000 HQI-TS D/S



14014394
Aluminium power supply unit IP65,
400 V - 50 Hz, class I, for 2000 W HQI-TS
D/S lamps without ignitor




14020601
Power supply unit 400 V - 50 Hz, class
I, on galvanised steel plate for 2000W
metal halide lamps (not for HQI-TS
and HQI-TS High Flux) with fuse and
without ignitor



14014420
Set including power supply unit and
power-factor capacitor for 2000W HQI-
TS 400V 50 Hz lamp

OPTIONAL ACCESSORIES

RAY



14013720
Stainless steel wire guard



14166494
RAY Bracket with slots to allow the
luminaire to be turned transversally
and longitudinally