


MIMIK 20 FLAT M




Part number	303745
Lampholder:	LED
Light Source:	LED
Wattage:	13,5 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	1710 lm
Luminaire lumen output:	1042 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	45°




Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
 - Flat, microprismatic tempered glass diffuser, screen printed on the inner surface for MIMIK FLAT series
 - Silicone gasket
 - LED versions include 220/240 V 50/60 Hz safety transformer
 - "MIMIK fixtures are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
 - Powder polyester painting process optimized against UV rays in 13 different steps
 - M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK FLAT M



310441
FLAT M Customising ring / Facade
Accessory