



MIMIK 20 FLAT B




Part number	303748
Lampholder:	LED
Light Source:	LED
Wattage:	24 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	3420 lm
Luminaire lumen output:	2095 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°




Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
 - Flat, microprismatic tempered glass diffuser, screen printed on the inner surface for MIMIK FLAT series
 - Silicone gasket
 - LED versions include 220/240 V 50/60 Hz safety transformer
 - "MIMIK fixtures are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
 - Powder polyester painting process optimized against UV rays in 13 different steps
 - Double-emission (B) versions are equipped with two lights in order to provide upward and downward emission
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK FLAT B



310442
FLAT B Customising ring / Facade
Accessory