


# EKO+19/G LED




<b>Part number</b>	301645
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	10 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 2J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	738 lm
<b>Luminaire lumen output:</b>	235 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	40°



## Description

- Wall and ceiling mounting luminaire for indoor and outdoor, comprising:
- Die-cast painted aluminium housing, ring and screens
  - Pressed glass diffuser, white painted inside
  - EPDM gasket
  - Diffuser stays securely hinged to the frame
  - No through wiring
  - Stainless steel locking screws
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

