

Products /  **CASTALDI** / THOR D51 / D51 THOR/0 / D51/0-MLWW-VN

## THOR D51 D51/0-MLWW-VN

### TECHNICAL DATA

#### GENERAL



Item code	D51/0-MLWW-VN
Place installation	outdoor
Name	D51 THOR/0 / D51/0-MLWW-VN wall recessed, low pole/bollard, wall mounted
Standard colour	VN - black glass
Environments	urban landscape, façades and architectural works, wellness, hallway, places of worship




#### PHYSICAL

Installation type	wall recessed, low pole/bollard, wall mounted
Mounting type	ground surface, surface, with rough-in housing
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Body	Corrosion resistant die-cast aluminium body.




#### DIMENSIONS

A: Total width device (mm)	85
L: Total length device (mm)	190
Built-in shaped	Rectangular
Built-in depth (mm)	65
Weight (kg)	1
Volume piece packed (m3)	0,003




#### OPTICAL SYSTEMS

Opening beam	asymmetric
Optical System	Safety tempered glass.
Reflectors	Extra-pure aluminium reflector.



## ENERGY SAVING

This luminaire contains built-in LED lamps  
The lamps cannot be changed in the luminaire





## SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature Colour	Nominal Flux	Output Flux	Source description
LED	-	6W	-	-	3000K	-	156 lm	-

## ELECTRICAL

Ballast type	Electronic
Mounting ballast type	Integral
Line input	Line entry: use only H07RN-F cable (EN 60598-1) with diameter between 7,5 and 12mm.
Voltage	220-240V
Frequency	50-60Hz

## PHOTOMETRICS



## NORMS / DIRECTIVES


Norms	EN 60598-1, EN 60598-2-2
Directives	2014/35/UE, 2014/30/UE

## ACCESSORIES

## OPTIONAL ACCESSORIES


### Mounting

Accessory code	D51/0-MS-AL
Technical description	For models D51 thor/0. Wall bracked installation. -AL ALUMINIUM
A: Total width device (mm)	85
Body	Stainless steel support. Powder coat painting after multi-layer polyester pre-treatment for corrosion resistance.



### Pole

Accessory code	D51/0-CM-AL
Technical description	For models D51 thor/0. Folded stainless steel floor installation braked. Fixing on concrete base or suitable paving. -AL ALUMINIUM
A: Total width device (mm)	195
H: Total height device (mm)	300
Body	AISI 304 independent stainless steel bearing base. Powder coat painting after multi-layer polyester pre-treatment for corrosion resistance.



### Rough-in housing

<b>Accessory code</b>	<b>D51/0-CI</b>
<b>Technical description</b>	<b>For models D51 thor/0. Rough-in housing high stress resistance composite technopolymer.</b>
<b>A: Total width device (mm)</b>	<b>90</b>
<b>Built-in depth (mm)</b>	<b>65</b>

