


## SPILLO




<b>Part number</b>	303501
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	44 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	II
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK10 20J xx9
<b>CRI:</b>	70
<b>Kelvin:</b>	4000
<b>Lightsource lumen output:</b>	5236 lm
<b>Luminaire lumen output:</b>	3301 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	25°




### Description

- Post mounted outdoor luminaire for general lighting, including:
- Polyester powder coated die-cast aluminium housing
  - Fixing kit for posts Ø 60 - Ø 76 mm made of polyester powder-coated die-cast aluminium
  - Anti-aging silicone gasket
  - Waterproof cable gland M25x1.5 for cables Ø 9- Ø 14 mm
  - External electrical connection with sealed plug-socket QUICK, complete with cable
  - LED versions include 220/240 V 50/60 Hz safety transformer
  - Analogue dimmable HF ballast, 1-10 V
  - Each LED is coupled with an electronic safety device (NUD) that can by-pass it in case of failure
  - Stainless steel external screws
  - The "SECURE LIGHT DISTRIBUTION" system guarantees uniform light distribution even in the remote case of LED failures
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - Class II
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## OPTIONAL ACCESSORIES


### SPILLO




310403  
Pole top adaptor Ø 60 mm




310405  
Pole top adaptor Ø 76 mm



315023  
Pole Spillo INT. 3.3 m



315024  
Pole Spillo F.T. 2.8 m with flange



310415  
Baseplate Spillo