



# QUASAR 20 M




<b>Part number</b>	303540
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	12,5 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	1138 lm
<b>Luminaire lumen output:</b>	407 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	30°



## Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
  - Glass diffuser, internally painted for homogeneous diffused light
  - Reflector in satin finish pure aluminium (Al 99.98)
  - Silicone gasket
  - High frequency electronic ballast supplied as standard
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

