


# MINI LED FL-O S/EW




<b>Part number</b>	06175487
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	42 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP20
<b>IK-J-xxIP:</b>	IK09 10J xx7
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	5796 lm
<b>Luminaire lumen output:</b>	2769 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°



## Description

- Extruded aluminium profile housing, painted
- Opal technopolymer diffuser
- Technopolymer end caps
- Symmetrical optics
- Fast male-female connector, for wires Ø 7.5 - Ø 12 mm
- Light beam obtained by the combination of multiple LED modules
- Stainless steel external screws
- Stainless steel springs for quick ceiling mount Surface mounted LED batten, suitable for edge and cove lighting, comprising:
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

