


## INSERT+ 1




<b>Part number</b>	304118
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	7 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK07 2J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COSφ ≥ 0,9
<b>Optic:</b>	ASYMMETRIC MEDIUM REFLECTOR
<b>Lightsource lumen output:</b>	825 lm
<b>Luminaire lumen output:</b>	250 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-10°
<b>Ta MAX luminaire:</b>	35°




### Description

- Wall recessed luminaire, for indoor and outdoor comprising:
- Polyester powder coated die-cast aluminium housing
  - Diffuser in flat glass, internally frosted
  - EPDM gasket
  - External electrical connection with sealed plug-socket QUICK, complete with cable
  - Electrical connector for wires Ø 7 - Ø 12 mm
  - Stainless steel locking screws
  - The fixture requires recessed fixing box which must be ordered separately
  - The recessed box is equipped with a removable cover and provided with two spirit levels to facilitate the installation process
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## MANDATORY ACCESSORIES

### INSERT+ 1



310475  
Recessed box INSERT+ 1

## OPTIONAL ACCESSORIES

### INSERT+ 1



310478  
Adaptor INSERT+ 1