


EKO+26 LED DETEK HF



Part number	303636
Lampholder:	LED
Light Source:	LED
Wattage:	18 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	2226 lm
Luminaire lumen output:	1161 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°




Description

Wall and ceiling mounting luminaire for indoor and outdoor, comprising:

- Die-cast painted aluminium housing, ring and screens
- Pressed glass diffuser, white painted inside
- Diffuser stays securely hinged to the frame
- EPDM gasket
- Stainless steel locking screws
- No through wiring
- LED SMD versions are complete with mid-power boards
- Tilting LED board for easy wiring during installation
- Maximum switchable load 400 W for incandescent lamps or 200 W for fluorescent lamps
- Hyper-frequency (HF) sensor operating at a frequency of 5.8 Ghz+/- 75 Mhz
- Fully adjustable daylight sensor (5-1000 lux), timing sensor (10-300 s) and sensitivity sensor (20-100%)
- The integrated protection module inside the sensor allows the installation of more than one luminaire in the same room without the risk of reciprocal interference
- Widest detection field up to 8 meters
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

