


# QUASAR 10 4WB




<b>Part number</b>	303350
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	10,8 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP44
<b>IK-J-xxIP:</b>	IK02 0.20J xx0
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	GRAZING REFLECTOR
<b>Lightsource lumen output:</b>	600 lm
<b>Luminaire lumen output:</b>	329 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-10°
<b>Ta MAX luminaire:</b>	25°



## Description

- Indoor and outdoor wall-mount fixture, including:
- Die-cast painted aluminium housing
  - Integral clear flat glass diffuser
  - Polymer gasket
  - Stainless steel fastening screws and dowels
  - Built-in driver
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

