


NORMA+ 60




Part number	305948
Lampholder:	LED
Light Source:	LED
Wattage:	18 W
Finish:	GR-RAL7035 / Grey RAL7035 / Matt
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK09 15J xx7
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	2718 lm
Luminaire lumen output:	2246 lm
L:	L80
B:	B10
Lifetime:	44000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	45°



Description

- Weatherproof luminaire with LED light source, comprising:
- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
 - Technopolymer end caps
 - Anti-aging silicone gasket
 - Polycarbonate bushing for the power connection with bayonet opening without utensils.
 - Cable gland M20x1.5 for cables $\varnothing 10$ - $\varnothing 14$ mm
 - Light beam obtained by the combination of multiple LED modules
 - Aluminium heat dissipation system
 - Stainless steel springs for quick ceiling mount
 - Supplied with anti-vacuum valve
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

