

## NORMA+ 150 CL




<b>Part number</b>	305994
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	60 W
<b>Finish:</b>	GR-RAL7035 / Grey RAL7035 / Matt
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK09 15J xx7
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	9060 lm
<b>Luminaire lumen output:</b>	7556 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	44000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	40°




### Description

- Weatherproof luminaire with LED light source, comprising:
- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
  - Technopolymer end caps
  - Anti-aging silicone gasket
  - Luminaire complete with through wiring for power supply to a continuous row
  - Dimmable DALI
  - Light beam obtained by the combination of multiple LED modules
  - Aluminium heat dissipation system
  - Stainless steel springs for quick ceiling mount
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### NORMA+ 150



14431995

Galvanized steel protection grills, to  
be fixed on ceiling