


MULTI+ 40 PC




Part number	304127
Lampholder:	LED
Light Source:	LED
Wattage:	28 W
Finish:	WH-87 / White / Textured
Insulation class:	II
Degree of protection:	IP65
IK-J-xxIP:	IK10 20J xx9
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	4284 lm
Luminaire lumen output:	2278 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°




Description

- Wall and ceiling mounting luminaire for indoor and outdoor, comprising:
- Technopolymer housing
 - Opal diffuser manufactured from technopolymer, 960°C glow wire test rated
 - Class II
 - Silicone gasket
 - Through-wiring possible
 - Stainless steel, anti-tamper locking screws
 - Max 20 mm diameter for cable/conduit entry
 - Supplied with SMD self-heat dissipating power LED metal core board: FUTURE-PROOF™
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

MULTI+ 40 PC



310514
Tool TORX