

WIN+2 WR




Part number	06266394
Lampholder:	LED
Light Source:	LED
Wattage:	139 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 2.4J xx5
CRI:	70
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
Optic:	ROAD REFLECTOR
Lightsources lumen output:	17800 lm
Luminaire lumen output:	15483 lm
L:	L70
B:	B10
Lifetime:	55000 h
Ta MIN luminaire:	-40°
Ta MAX luminaire:	35°




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - High-transparency polycarbonate lenses for best light transmission
 - Anti-aging silicone gasket
 - Fully integrated technopolymer trim hinged to the housing
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Light beam obtained by the combination of multiple LED modules
 - Stainless steel external screws
 - Powder coated steel bracket
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

WIN+2



14045694
External anti-glare louvre painted aluminium grey (WIN+2)



14045794
External steel cowl painted aluminium grey (WIN+2)



14068694
Aluminium pole top and steel outreach arm. Painted aluminium grey (WIN+2)



14068794
Twin WIN+2 aluminium pole top fitting and steel outreach arm for Ø76mm poles, installed at 90°. Painted aluminium grey



14068894
Twin WIN+2 aluminium pole top fitting and steel outreach arm for Ø 76 mm poles, installed at 180°. Painted aluminium grey



14068994
Three WIN+2 aluminium pole top fitting and steel outreach arm for Ø 76 mm poles, installed at 90°. Painted aluminium grey



14069094
Three WIN+2 aluminium pole top fitting and steel outreach arm for Ø 76 mm poles, installed at 120°. Painted aluminium grey



14069194
Four WIN+2 aluminium pole top fitting and steel outreach arm for Ø 76 mm poles. Painted aluminium grey



14057394
Long bracket for ceiling mounting, painted aluminium grey (WIN+2)



14046120
WIN+2 strengthening bracket. Suitable for one floodlight single point fixing M12 screw in centre of the bracket



14048694
1000mm extension arm in heavy gauge steel, painted aluminium grey (WIN+2)



14051294
Single pole top mounting, for Ø 60-76 mm poles, painted aluminium grey



14051394
Double pole top mounting, Ø 60-76mm poles, painted aluminium grey