

SQUARE+2 A/W




Part number	06263996
Lampholder:	LED
Light Source:	LED
Wattage:	139 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	II
Degree of protection:	IP66
IK-J-xxIP:	IK07 2.4J xx5
CRI:	70
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	17800 lm
Luminaire lumen output:	15013 lm
L:	L70
B:	B10
Lifetime:	55000 h
Ta MIN luminaire:	-40°
Ta MAX luminaire:	35°




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - High-transparency polycarbonate lenses for best light transmission
 - Asymmetrical optic
 - Anti-aging silicone gasket with high resiliency
 - Fully integrated painted die-cast aluminium trim hinged to the housing
 - Electrical connection through an IP66 quick external socket-plug connector that makes it possible to connect it to the network without opening the lighting element, made of techno-polymer, 5 poles x 4 mm², for wires ø 10 - ø 14 mm
 - Light beam obtained by the combination of multiple LED modules
 - Stainless steel external screws
 - Complete with supplementary device for protection against network surges of up to 10 kV (DM)
 - A wide range of accessories are available for floodlight installation in various situations, e.g. wall and post
 - In order to allow for the use of lenses in typical urban furniture settings (parks, gardens, pedestrian areas, squares, parking areas, etc.), the SYSTEMPARK range of accessories is available. They offer a range of stainless steel posts and painted aluminium arms that

Photometric data



Technical drawings



make it possible to solve a variety of installation requirements.

- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

OPTIONAL ACCESSORIES

SQUARE+2 SYSTEMPARK




14473196
Pole arms for SQUARE+2

SQUARE+1/2 SYSTEMPARK




14099696
Gliding support made of painted aluminium for the installation on Ø 90 mm posts


POLE SQUARE+1/2 SYSTEMPARK



14099004
Pole Ø 90 mm INT. (buried) 5+1 m




14098704
Pole Ø 90 mm / Ø 3,54 F.T. 3,5 m c/w flange




14098904
Pole Ø 90 mm / Ø 3,54 F.T. 6 m c/w flange

ANCHOR KIT SQUARE+1/2 SYSTEMPARK



310923
Flange plate fixing root



14099220
Base plate/1 F.T. post

SQUARE+2 SOLUTION



14111296
Single pole top arm Ø 76 mm SQUARE+2



14111396
Double arm at 90° with pole top Ø 76 mm SQUARE+2



14111496
Double arm at 180° with pole top Ø 76 mm SQUARE+2



14111596
Triple arm at 90° with pole top Ø 76 mm SQUARE+2



14111696
Triple arm at 120° with pole top Ø 76 mm SQUARE+2



14111796
Quadruple pole top arm Ø 76 mm SQUARE+2



14111896
Wall-mounting arm SQUARE+2



14472996
Arms for SQUARE+2

SQUARE+2 SOLUTION WING POLE F.T.



14126096
SQUARE WING with 7.2 m high pole and base plate with single arm for SQUARE+2



14125996
SQUARE WING with 6.2 m high pole and base plate with single arm for SQUARE+2



14126196
SQUARE WING with 8.2 m high pole and base plate with single arm for SQUARE+2



14126296
SQUARE WING with 6.2 m high pole and base plate with double arm for SQUARE+2



14126396
SQUARE WING with 7.2 m high pole and base plate with double arm for SQUARE+2



14126496
SQUARE WING with 8.2 m high pole and base plate with double arm for SQUARE+2

SQUARE+2 SOLUTION WING POLE INT.



14126996
SQUARE WING with 6.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14127096
SQUARE WING with 7.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14127196
SQUARE WING with 8.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14127296
SQUARE WING with 6.2 m + 0.8 m high pole to be buried for floor mounting, with double arm for SQUARE+2



14127396
SQUARE WING with 7.2 m + 0.8 m high pole to be buried for floor mounting, with double arm for SQUARE+2



14127496
SQUARE WING with 8.2 m + 0.8 m high pole to be buried for floor mounting, with double arm for SQUARE+2

SQUARE+2 SOLUTION BAR POLE F.T.



14123996
SQUARE BAR with 6.2 m high pole and base plate with single arm for SQUARE+2



14124096
SQUARE BAR with 7.2 m high pole and base plate with single arm for SQUARE+2



14124196
SQUARE BAR with 8.2 m high pole and base plate with single arm for SQUARE+2



14124296
SQUARE BAR with 6.2 m high pole and base plate with double arm for SQUARE+2



14124396
SQUARE BAR with 7.2 m high pole and base plate with double arm for SQUARE+2



14124496
SQUARE BAR with 8.2 m high pole and base plate with double arm for SQUARE+2

SQUARE+2 SOLUTION BAR POLE INT.



14124996
SQUARE BAR with 6.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14125096
SQUARE BAR with 7.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14125196
SQUARE BAR with 8.2 m + 0.8 m high pole to be buried for floor mounting, with single arm for SQUARE+2



14125296
SQUARE BAR with 6.2 m + 0.8 m high pole to be buried for floor mounting, with double arm for SQUARE+2



14125496
SQUARE BAR with 8.2 m + 0.8 m high
pole to be buried for floor mounting,
with double arm for SQUARE+2



14125396
SQUARE BAR with 7.2 m + 0.8 m high
pole to be buried for floor mounting,
with double arm for SQUARE+2