

NOTTURNO 500




Part number	304899
Lampholder:	LED
Light Source:	LED
Wattage:	20 W
Finish:	GR-11 / Anodised grey / Matt
Insulation class:	III
Degree of protection:	IP66
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Lightsource lumen output:	2016 lm
Luminaire lumen output:	1623 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-30°
Ta MAX luminaire:	50°




Description

- Indoor and outdoor wall-mount fixture, including:
- Extruded anodised aluminium housing
 - Tempered glass diffuser, printed
 - Class III
 - Shank connection in Stainless Steel AISI 304
 - Symmetrical lens
 - Aluminium heat sink
 - For the installation of the product must be used the appropriate brackets available as an accessory
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



CONTROL GEAR

NOTTURNO




310542
Power Supply Unit L500

MANDATORY ACCESSORIES

NOTTURNO



310523
Bracket NOTTURNO (nr. 2)



310524
Bracket (nr. 2)



310978
NOTTURNO Telescopic bracket



310981
NOTTURNO ground support bracket