

DLSB220 LED OPAL COVER - 95 MM




Part number	822720833001
Lampholder:	LED
Light Source:	LED
Wattage (W):	18 W
Finish / RAL:	White RAL9016
Insulation class:	I
Degree of protection:	IP 20
Kelvin:	3000
Power factor:	COSφ ≥ 0,9
EEL:	A2
Optic:	EXTRA WIDE CIRCLE REFLECTOR (=>75°)
Optic Beam:	2 x 47°
Lightsource lumen output:	2070 lm
Luminaire lumen output:	1630 lm
Lifetime:	50000 h
Percent lumen depreciation:	L80



Description

- Recessed round LED downlight for indoors, consisting of:
- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
 - Light-tight housing
 - Suitable for ceiling tile thickness from 1-25 mm
 - Recessed frosted diffuser for optimal light distribution and high homogeneity
 - White modular reflector, ABS injection-molded with light-tight connection of LED board
 - Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
 - Colour rendering index Ra > 80
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Also dimmable via TouchDIM®
 - Complete with electric converter
 - Protection class IP54* (for light emission surface for installation in closed ceilings)

TECHNICAL DATA



TECHNICAL DRAWINGS

