



THB.406.C8A

MADE IN ITALY

TH406 - Plug&Socket connector panel-mounted IP68



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP68 Plug&Socket circular connectors
Product name (Series)	TH406 - Plug&Socket connector panel-mounted IP68
Product configuration	Connettore Presa <i>* Fixing nut included in the kit.</i>
Thread	M28
Panel thickness min. - max.	max 12.0 mm
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 36.5 mm x 70 mm (when plug-socket matched)

ELECTRICAL CHARACTERISTICS

Number of poles	8
Contact marking	1-2-3-4-5-6-7-E
Type of connection	screw (M2 - max. 0.2 Nm)
Operating current	max. 10A AC/DC
Operating voltage	max. 400V AC (60V DC)
Impulse withstand voltage	2.5kV

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (10m/1h)
Protection against impact (IK)	IK08
Corrosion resistance	Salt mist test : EN60068-2-11:2000

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.25 mm ² - 1.0 mm ²
---	--

MATERIAL CHARACTERISTICS

Body	PA66 UL94 V2 GWT 850°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free - Silicone Free
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

INDUSTRY STANDARDS

Standard number	EN 61984:2009
-----------------	---------------

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 pz



Box dimension 400x400x230 mm

INSTALLATION INSTRUCTIONS

- TH405 - TH406 ENG PDF • 839 KB
- TH405 - TH406 ITA PDF • 831 KB