



**FUSIBILI ASSIALI G4**  
G4 axial type fuses | *Fusibles axiaux G4*

**Corrente resistiva**  
10 A - 250 V / 15 A - 120 V

**Corrente induttiva**  
8 A - 250 V / 14 A - 120 V

**Tolleranza**  
+0°C -5°C

**Terminali**  
(D) rame stagnato  
(E) rame argentato

**Codice omologazione**  
Thermodisc G4

**Norme riferimento**  
EN 60691 UL - 1020  
C22.2 n°209

**Resistive current**  
10 A - 250 V / 15 A - 120 V

**Inductive current**  
8 A - 250 V / 14 A - 120 V

**Tolerance**  
+0°C -5°C

**Contacts**  
(D) tin plated copper  
(E) silver plated copper

**Approval code**  
Thermodisc G4

**Standards**  
EN 60691 UL - 1020  
C22.2 n°209

**Courant de résistance**  
10 A - 250 V / 15 A - 120 V

**Courant d'induction**  
8 A - 250 V / 14 A - 120 V

**Tolérance**  
+0°C -5°C

**Contacts**  
(D) cuivre étamé  
(E) cuivre argenté

**Code d'homologation**  
Thermodisc G4

**Normes**  
EN 60691 UL - 1020  
C22.2 n°209



pag. 220-221



| <b>Codice</b> | <b>T. temperatura</b> | <b>T<sub>F</sub> °C</b> | <b>T<sub>H</sub> °C</b> | <b>T<sub>M</sub> °C</b> |
|---------------|-----------------------|-------------------------|-------------------------|-------------------------|
| Code          | T. temperature        | T <sub>F</sub> °C       | T <sub>H</sub> °C       | T <sub>M</sub> °C       |
| Code          | T. température        | T <sub>F</sub> °C       | T <sub>H</sub> °C       | T <sub>M</sub> °C       |

**Terminali 16-35 | 16-35 Contacts | Contacts 16-35**

|           |      |      |      |      |
|-----------|------|------|------|------|
| G4A00072C | 72°  | 72°  | 57°  | 100° |
| G4A00077C | 77°  | 77°  | 62°  | 125° |
| G4A00084C | 84°  | 84°  | 69°  | 125° |
| G4A00093C | 93°  | 93°  | 78°  | 140° |
| G4A00098C | 98°  | 98°  | 83°  | 140° |
| G4A00104C | 104° | 104° | 89°  | 150° |
| G4A00110C | 110° | 110° | 95°  | 150° |
| G4A00117C | 117° | 117° | 102° | 160° |
| G4A00121C | 121° | 121° | 106° | 160° |
| G4A00128C | 128° | 128° | 113° | 205° |
| G4A00144C | 144° | 144° | 129° | 240° |
| G4A00152C | 152° | 152° | 137° | 205° |
| G4A00167C | 167° | 167° | 152° | 240° |
| G4A00184C | 184° | 184° | 169° | 210° |
| G4A00192C | 192° | 192° | 177° | 210° |
| G4A00216C | 216° | 216° | 200° | 375° |
| G4A00229C | 229° | 229° | 200° | 375° |
| G4A00240C | 240° | 240° | 200° | 450° |

**Terminali 35-35 | 35-35 Contacts | Contacts 35-35**

|           |      |      |      |      |
|-----------|------|------|------|------|
| G4A01072C | 72°  | 72°  | 57°  | 100° |
| G4A01077C | 77°  | 77°  | 62°  | 125° |
| G4A01084C | 84°  | 84°  | 69°  | 125° |
| G4A01093C | 93°  | 93°  | 78°  | 140° |
| G4A01098C | 98°  | 98°  | 83°  | 140° |
| G4A01104C | 104° | 104° | 89°  | 150° |
| G4A01110C | 110° | 110° | 95°  | 150° |
| G4A01117C | 117° | 117° | 102° | 160° |
| G4A01121C | 121° | 121° | 106° | 160° |
| G4A01128C | 128° | 128° | 113° | 205° |
| G4A01144C | 144° | 144° | 129° | 240° |
| G4A01152C | 152° | 152° | 137° | 205° |
| G4A01167C | 167° | 167° | 152° | 240° |
| G4A01184C | 184° | 184° | 169° | 210° |
| G4A01192C | 192° | 192° | 177° | 210° |
| G4A01216C | 216° | 216° | 200° | 375° |
| G4A01229C | 229° | 229° | 200° | 375° |
| G4A01240C | 240° | 240° | 200° | 450° |



2000 pz  
2000 pcs  
2000 pces



pronta  
in stock  
en stock



a richiesta sono disponibili in bandoliera da 4.500 pz.  
reel of 4.500 pcs. available upon request  
sur demande, ils sont disponibles en bande  
de 4.500 pces