

**HEADERS
FOR PCB.**

**CONNETTORI MASCHIO
PER C.S.**

**CONNECTEURS MÂLE
POUR C.I.**


**STIFTLISTE
FÜR LEITERPLATTEN**

CPM..FV **CPM..SQ*FV**

Single block - Blocco unico
Monobloc - Einzelblock

Poles - Pôles - Polzahl

2/10




MRT21 **MRT21..SQ***

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensetzbare Blöcke

Poles - Pôles - Polzahl

2/3




MRT21 **MRT21..SQ***

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensetzbare Blöcke

Poles - Pôles - Polzahl

2/3



MRT21 **MRT21..SQ***

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensetzbare Blöcke

Poles - Pôles - Polzahl

1/2




MRT21 **MRT21..SQ***

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensetzbare Blöcke

Poles - Pôles - Polzahl

1/2



Pitch Passo	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Nominal voltage Bemessungsspannung	V
Rated Current Intensità nominale	Nominal current Bemessungsstrom	A
Temperature Temperatura	Temperature Temperatur	°C
Housing Corpo isolante	Insulating body Isoliertes Gehäuse	



IMQ	EN61984
VDE	EN61984
cUL	UL1059 + C22 2 n°158

Poles Pôles	Pol Polzahl	X
Colors Couleurs	Color Farben	Y
Other information Autres données	Other data Weitere Informationen	P

CPM 10 / X	FV	Y	N...
Type Tipo	Pitch Passo	Poles Poli	Version Versione
Type Tipo	Pitch Passo	Poles Poli	Version Versione
Type Tipo	Pitch Passo	Poles Poli	Version Versione



10 - 10,16	630	20
110	PA - UL 94 V0	
V	A	mm ² /AWG
630	20	0,2 - 2,5
630	20	0,2 - 2,5
300	12	24 - 12

min 2 - max 10		
VE	/ on demand	GR GR NE AR BL RO GI
D/B4		





5	320	20
110	PA - UL 94 V0	
V	A	mm ² /AWG
320	20	0,2 - 2,5
320	20	0,2 - 2,5
300	12	30 - 12

min 2 - max ...		
VE	/ on demand	GR GR NE AR BL RO GI
D/B4		





5,08	320	20
110	PA - UL 94 V0	
V	A	mm ² /AWG
320	20	0,2 - 2,5
320	20	0,2 - 2,5
300	12	30 - 12

min 2 - max ...		
VE	/ on demand	GR GR NE AR BL RO GI
D/B4		





10	630	20
110	PA - UL 94 V0	
V	A	mm ² /AWG
630	20	0,2 - 2,5
630	20	0,2 - 2,5
300	12	30 - 12

min 2 - max ...		
VE	/ on demand	GR GR NE AR BL RO GI
D/B4		



10,16	630	20
110	PA - UL 94 V0	
V	A	mm ² /AWG
630	20	0,2 - 2,5
630	20	0,2 - 2,5
300	12	30 - 12

min 2 - max ...		
VE	/ on demand	GR GR NE AR BL RO GI
D/B4		



* SQ Version = Horizontal version