



Saves Your Energy

PRODUCT CARD

9/13/16

## NAC31.B

3-pólový konektor bez odlehčení tahu, vidlice

Kód	NAC31.B
GTIN	6418677113895
Název	3-pólový konektor bez odlehčení tahu, vidlice EnstoNet Bílá (1, PE, N)
Popis	Pro pružné, slaněné a plné dráty. Průřezy vodičů: 0,75-4,0 mm <sup>2</sup> . Váha 10,1 g. Póly značeny v závorkách.
Dodavatel	Ensto Finland Oy



## Technické parametry

### Technické údaje

UL Wire range: 12 ... 18 AWG

### Dimensions

Weight: 9.8 g  
 Conductor cross-section: 0,75 - 4 mm<sup>2</sup>  
 Dimensions l x w x h: 32x39x18

### Temperatures

Max. operating temperature: +70 °C  
 Min. installation temperature: +5 °C

### Colors

Color: Black

### Features

Pole markings: 1,PE,N

### Drawing markings

L: 250 mm

## Ratings

Rated voltage:	250 V
Degree of protection:	IP20
Rated current:	20 A
ETIM:	EC002560

## US specific

UL Rated voltage:	250 V
UL Rated current:	16 A

## ETIM

---

### ETIM

Width:	39 mm
Length:	32 mm
Height:	18 mm

## Balení

---

### Balení

Unit:	PCS
Size:	200
Length:	220 mm
Width:	220 mm
Height:	125 mm
Weight (brt):	2.056 kg
Volume:	6.05

### Pallet package

Size:	25000
Length:	1200 mm
Width:	800 mm
Height:	1150 mm

