



Saves Your Energy

PRODUCT CARD

9/13/16

NAC32S.B

3-pólový konektor s odlehčením tahu, zásuvka

Kód NAC32S.B
GTIN 6418677113956
Název 3-pólový konektor s odlehčením tahu, zásuvka EnstoNet
 Černá (1, PE, N)
Popis Pro pružné, slaněné a plné dráty. Průřezy vodičů 0,75-4,0 mm². Odlehčovač tahu pro kabely s vnějším průměrem 6,6-12,0 mm a NAC32SL.W pro 4,5-11,0 mm. Váha 16,8 g. Označení svorek viz. závorky.

Dodavatel Ensto Finland Oy



Technické parametry

Technické údaje

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 16.8 g

Conductor cross-section: 0,75 - 4 mm²

Dimensions l x w x h: 56x39x20

Temperatures

Max. operating temperature: +70 °C

Min. installation temperature: +5 °C

Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Black

Features

Pole markings: 1,PE,N

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 V

Degree of protection: IP20

Rated current: 20 A

ETIM: EC002560

US specific

UL Rated voltage: 250 V

UL Rated current: 16 A

ETIM

ETIM

Width: 39 mm

Length: 56 mm

Height: 20 mm

Balení

Balení

Unit: PCS

Size: 200

Length: 290 mm

Width: 285 mm

Height: 190 mm

Weight (brt): 3.6 kg

Volume: 15.7

Pallet package

Unit: PCS

Size: 10400

Length: 1200 mm

Width: 800 mm

Height: 1100 mm

Weight (brt): 213 kg

