



## fitted with

work equipment  
connected load  
power consumption  
luminous flux  
luminous efficacy  
illuminance efficiency factor  
light colour  
color rendering index (CRI)  
consistent white light of  
glare-free  
class of protection  
technology  
luminaire body  
lamp cover  
tubular sections  
balance of articulation joints  
weight (net)  
mains lead

## fastening

## special features

## LED

Energy efficiency category A+  
electronic plug-in transformer  
100-240 V; 50/60 Hz  
approx. 8 W  
approx. 600 lm  
approx. 75 lm/W  
92 lx/W  
neutral white, approx. 4000 K  
> 80 (typ. 85)  
< 4 SDCM  
plastic reflector  
II with plug-in power supply; III without plug-in power supply  
continuously dimmable  
aluminium, painted, white  
screen, clear  
tubular aluminium section, painted, white  
friction  
approx. 0.5 kg  
approx. 3 m; mains plug  
CEE 7/XVI  
adaptor (accessory), table base (accessory), table clamp (accessory)  
automatic switchoff adjustable, push button in luminaire head, behaviour at net recovery adjustable



\* Separate ENEC certification for luminaire and power supply




CEE 7/XVI

## illuminance

distance: 50 cm

Em: 736 lx  
Emax: 1088 lx  
Emin: 415 lx



## luminous intensity

