REGIOLUX

| SDGVOH LED 10000lm 840 - vw - ET - 1854040415 | SDGVOH LED | 10000lm 840 - vw - | - ET - 18540404150 |
|---|------------|--------------------|--------------------|
|---|------------|--------------------|--------------------|

| Category (ETIM): | Variable device mount |
|-------------------------------------|---|
| Туре: | Device mounts IP20 SDGVOH LED |
| Order number: | 18540404150 |
| Configuration: | LED, Colour rendering/Light colour CRI ≥ 80 / 4000K |
| LED service life: | 50000h L80/B10 |
| Operating device: | Electronic driver (1 pcs.) |
| Mains voltage: | 230V / 50Hz |
| System performance (W): | 75 |
| Luminaire luminous flux (Im): | 10000 |
| Luminaire luminous efficacy (Im/W): | 129 |
| Energy efficiency class: | A++ |
| Ambient temperatures: | 10°C/25°C |
| Certifications: | IP 20, protection class I, BAP 65°<3000, ENEC10 VDE, F, DIN10500/Food, Indoor, CE |
| Colour of the housing: | traffic white RAL 9016 |
| Weight (net) (kg): | 2 |
| Dimensions LxWxH/DxH (mm): | 1531 x 55 x 37 |
| mounting method: | Mounting rail system mounting |
| EAN-number: | 4020863325757 |
| Commodity code: | 94051098 |

Quick-fit mounting system Variable device mount; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Can be variably positioned on the mounting rail. Housing colour traffic white RAL 9016; Extremely direct narrow-beam light distribution with controlled rack lighting using individual. lens. optic made of PMMA plastic. Continuous optics. Uniform LED spacing, even across circuit boards. 3-row LED arrangement. Light direction components are easy to maintain due to smooth surface which is easily cleaned. Heat-resistant cables including connection cable 1m and rapid installation plug connector with phase preselection without tools and locating finger.


Dimensions LxWxH/DxH (mm): $1531 \times 55 \times 37$ Configuration: LED, Colour rendering/Light colour CRI $\ge 80 / 4000K$ LED service life: 50000h L80/B10Luminaire luminous flux (lm): 10000Luminaire luminous efficacy (lm/W): 129Operating device: Electronic driver (1 pcs.) System performance (W): 75Energy efficiency class: A++ Conditions: Suitable for use in ambient temperatures of $10^{\circ}C$ to $25^{\circ}C$ Certifications: IP 20, protection class I, BAP $65^{\circ}<3000$, ENEC10 VDE, F, DIN10500/Food, Indoor, CE

Regiolux GmbH Type: SDGVOH LED 10000 840 ET vw Article number: 18540404150 Product deep link: http://www.regiolux.de/de/article/18540404150 5 year guarantee after registration on website.



Lighting technology

Individual.Lens.Optic-direct extremely narrow distribution SDGVOH LED 10000 Im 840



37

★ 55 **★**

