

ACRO+ EQ258 HO



| | |
|--------------------------------|----------------------------------|
| Part number | 3103935 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 73 W |
| Finish: | GR-RAL7035 / Grey RAL7035 / Matt |
| Insulation class: | I |
| Degree of protection: | IP66 |
| IK-J-xxIP: | IK03 0.35J xx1 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COS ϕ \geq 0,9 |
| Optic: | Symmetric extra wide reflector |
| Luminaire lumen output: | 10200 lm |
| L: | L70 |
| B: | B50 |
| Lifetime: | 70000 h |
| Ta MIN luminaire: | -25° |
| Ta MAX luminaire: | 40° |




Description

Weatherproof LED luminaire complete with diffuser, comprising:

- Housing made of fiberglass reinforced polyester
- Opal PMMA diffuser for optimal light diffusion and a high light uniformity
- Silicone gasket
- 4000 K multichip LED board
- Stainless steel retaining clips
- Quick ceiling fixing bracket (stainless steel)
- EXTREME versions are suitable for extreme conditions, -40°C
- Emergency and extreme versions have a polycarbonate diffuser, 850°C glow wire
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

