

AS427 LED WIDE FLOOD REFLECTOR



Part number	3108547
Lampholder:	LED
Light Source:	LED
Wattage:	40 W
Finish:	WH-RAL9010 / White RAL9010 / Textured
Insulation class:	II
Degree of protection:	IP20
IK-J-xxIP:	IK02 0.20J xx0
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
EEL:	A2
Optic:	Wide circle medium reflector
Optic Beam:	2 x 34°
Lightsource lumen output:	5190 lm
Luminaire lumen output:	4330 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°




Description

LED track light for indoor, comprising:

- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Bayonet-closure ring for a toolless replacement of the reflector and the louvre
- Reflector in Wide Flood design
- Colour tolerance according to MacAdam \leq 3 SDCM
- Colour rendering index Ra > 80
- LED lifetime 60.000 h at 80% luminous flux (L80B10)
- Universal tri-phase adaptor included
- Built-in driver
- Quick installation without tools
- Clear safety glass
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®

Photometric data



Technical drawings

