

AS448 LED FLOOD REFLECTOR



Part number	8448473323410
Lampholder:	LED
Light Source:	LED
Wattage:	35 W
Finish:	WH-RAL9010 / White RAL9010 / Textured
Insulation class:	II
Degree of protection:	IP20
IK-J-xxIP:	IK02 0.20J xx0
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
EEL:	A2
Optic:	Flood Circle Reflector
Optic Beam:	2 x 27°
Lightsource lumen output:	4400 lm
Luminaire lumen output:	3520 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°




Description


LED track light for interior, including:

- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum lamp performance and neutral colour rendering
- Bayonet-closure ring for a toolless replacement the of the reflector and the louvre
- Reflector in Flood design
- Colour tolerance according to MacAdam \leq 3 SDCM
- Rated LED service life of 50,000 hrs before luminance drops to 80 % (L80B10 50.000h)
- Universal tri-phase adaptor included
- Complete with electric converter
- Quick installation without tools
- Complete with clear safety glass pane

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

AS 448



8417900
Frosted safety glass pane



8435961
Food glass filter for meat products



8435962
Food glass filter for bakery products



8435963
Food glass filter for fruits and cheese



8435964
Food glass filter for vegetables



8435965
Food glass filter for fish products