


A+ 200 C/EW



| | |
|----------------------------------|---------------------------------------|
| Part number | 3111276 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 200 W |
| Finish: | BK-RAL9005 / Black RAL9005 / Textured |
| Insulation class: | I |
| Degree of protection: | IP65 |
| IK-J-xxIP: | IK08 5J xx5 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COSφ ≥ 0,9 |
| Optic: | Extra wide circle reflector |
| Lightsource lumen output: | 32000 lm |
| Luminaire lumen output: | 27222 lm |
| L: | L80 |
| B: | B10 |
| Lifetime: | 60000 h |
| Ta MIN luminaire: | -40° |
| Ta MAX luminaire: | 45° |




Description


Suspended LED luminaire for indoor and outdoor industrial applications, comprising:

- Die-cast aluminium housing and trim painted with polyester powder coating after chemical conversion surface treatment
- Diffuser with integrated louvre in UV, heat stabilised, transparent technopolymer
- High resiliency anti-ageing silicone gasket with high elastic return capacity
- 4000 K multichip LED board
- Stainless steel locking screws
- Suspension hook in painted aluminium with safety screw
- Complete with cable H05RN-F
- Built-in driver
- Options:
 - Painted steel bracket
 - Infrared remote control for sensor module
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

A+



3111283
Fixing bracket A+200
Black RAL9005


A+ 100 / A+ 150 / A+ 200



3111277
Microwave motion sensor



3111278
Remote control A+



3111279
DALI converter