

## BLIZ MARINE




<b>Part number</b>	3100279
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	13,5 W
<b>Finish:</b>	BR-10 / Natural brass / Glossy
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 2J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Symmetric extra wide reflector
<b>Lightsource lumen output:</b>	1680 lm
<b>Luminaire lumen output:</b>	745 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-10°
<b>Ta MAX luminaire:</b>	35°



### Description

- Wall and ceiling mounting luminaire for indoor and outdoor, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Die cast polished brass guard screen with vibratory finishing
  - Pressed glass diffuser, white painted inside
  - EPDM gasket
  - Supplied with SMD self-heat dissipating power LED metal core board: FUTURE-PROOF™
  - Stainless steel locking screws
  - Metals with natural finish surface may oxidise with age. To restore the original brightness use commercial metal polish
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

