

## CRICKET+ 15 C/M



|                                               |                               |
|-----------------------------------------------|-------------------------------|
| <b>Part number</b>                            | 3108361                       |
| <b>Lampholder:</b>                            | LED                           |
| <b>Light Source:</b>                          | LED                           |
| <b>Wattage:</b>                               | 14 W                          |
| <b>Finish:</b>                                | INOX / Stainless steel / Matt |
| <b>Insulation class:</b>                      | I                             |
| <b>Degree of protection:</b>                  | IP67                          |
| <b>IK-J-xxIP:</b>                             | IK09 16J xx7                  |
| <b>CRI:</b>                                   | 80                            |
| <b>Kelvin:</b>                                | 4000                          |
| <b>Power factor:</b>                          | COSφ ≥ 0,9                    |
| <b>Optic:</b>                                 | Medium circle reflector       |
| <b>Lightsource lumen output:</b>              | 1403 lm                       |
| <b>Luminaire lumen output:</b>                | 1203 lm                       |
| <b>L:</b>                                     | L90                           |
| <b>B:</b>                                     | B10                           |
| <b>Lifetime:</b>                              | 94000 h                       |
| <b>Classification of recessed luminaires:</b> | A1 A2 A3 A4 A5                |
| <b>Glass temperature:</b>                     | 45°                           |
| <b>Ta MIN luminaire:</b>                      | -20°                          |
| <b>Ta MAX luminaire:</b>                      | 50°                           |




### Description


Series of class I reduced depth in-ground luminaires, comprising:

- Black painted anodised die-cast aluminium housing
- Extra clear, tempered, flat glass diffuser
- High-transparency polycarbonate lenses grant an optimized light transmission
- Circular optic
- High resiliency anti-ageing silicone gasket with high elastic return capacity
- Die-cast aluminium trim painted coated with AISI 316 stainless steel (versions INOX)
- Aluminium heat sink
- Mains connection device WATER STOP
- Technopolymer recessed casing available as an accessory to guarantee driveability and designed to favour water drainage through the WATER DRAIN system
- Stainless steel external screws
- Floor mounted luminaires are subject to harsh conditions during use. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- If the device is accessible to the public, it is advisable to ensure that the glass temperature is compatible with the prevailing local installation standards. The temperature is indicated on the website, on the data sheet of each item.
- Rough-in kit fixing system designed for a safe installation even when it is not perfectly flush with the floor
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## MANDATORY ACCESSORIES

### CRICKET+ 15



3111136  
Recessed fixing kit