

CRICKET+ 15 A/M



Part number	3108366
Lampholder:	LED
Light Source:	LED
Wattage:	14 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP67
IK-J-xxIP:	IK09 16J xx7
CRI:	80
Kelvin:	3000
Power factor:	COSφ ≥ 0,9
Optic:	Asymmetric Medium Reflector - A5/M
Lightsource lumen output:	1300 lm
Luminaire lumen output:	671 lm
L:	L90
B:	B10
Lifetime:	94000 h
Classification of recessed luminaires:	A1 A2 A3 A4 A5
Glass temperature:	45°
Ta MIN luminaire:	-20°
Ta MAX luminaire:	50°




Description


Series of class I reduced depth in-ground luminaires, comprising:

- Black painted anodised die-cast aluminium housing
- Extra clear, tempered, flat glass diffuser
- High-transparency polycarbonate lenses grant an optimized light transmission
- Asymmetrical optic
- High resiliency anti-ageing silicone gasket with high elastic return capacity
- Die-cast aluminium trim painted
- Aluminium heat sink
- Mains connection device WATER STOP
- Technopolymer recessed casing available as an accessory to guarantee driveability and designed to favour water drainage through the WATER DRAIN system
- Stainless steel external screws
- Floor mounted luminaires are subject to harsh conditions during use. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- If the device is accessible to the public, it is advisable to ensure that the glass temperature is compatible with the prevailing local installation standards. The temperature is indicated on the website, on the data sheet of each item.
- Rough-in kit fixing system designed for a safe installation even when it is not perfectly flush with the floor
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



MANDATORY ACCESSORIES

CRICKET+ 15



3111136
Recessed fixing kit