


CRICKET+ 20 C/M




Part number	3108379
Lampholder:	LED
Light Source:	LED
Wattage:	26 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP67
IK-J-xxIP:	IK10 21J xx9
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Medium circle reflector
Lightsource lumen output:	2940 lm
Luminaire lumen output:	2536 lm
L:	L90
B:	B10
Lifetime:	94000 h
Classification of recessed luminaires:	A1 A2 A3 A4 A5
Glass temperature:	41°
Ta MIN luminaire:	-40°
Ta MAX luminaire:	35°




Description

- Series of class I reduced depth in-ground luminaires, comprising:
- Black painted anodised die-cast aluminium housing
 - Extra clear, tempered, flat glass diffuser
 - High-transparency polycarbonate lenses grant an optimized light transmission
 - Circular optic
 - High resiliency anti-ageing silicone gasket with high elastic return capacity
 - Die-cast aluminium trim painted
 - Aluminium heat sink
 - Mains connection device WATER STOP
 - Stainless steel external screws
 - Recessed housing manufactured from technopolymer. Order separately
 - Floor mounted luminaires are subject to harsh conditions during use. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
 - Do not install luminaires in sunken areas
 - If the device is accessible to the public, it is advisable to ensure that the glass temperature is compatible with the prevailing local installation standards. The temperature is indicated on the website, on the data sheet of each item.
 - Rough-in kit fixing system designed for a safe installation even when it is not perfectly flush with the floor
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



MANDATORY ACCESSORIES

CRICKET+ 20



3111135
CONTROCASSA CRICKET+ 20