


NASTER D49 / D49 NASTER CEILING RECESSED / NASTER/C LED RGBW WALL GRAZING / D49/C4-RGBW-WG-AL

Product Info




Item code	NASTER D49 / D49/C4-RGBW-WG-AL
Category	Downlight
Environments	façades and architectural works, hallway, industrial areas, railway areas, subway areas
Mounting type	frame
Mounting note	In case of installation of a row of more fixtures the distance between the two adjacent holes (short side) must not be less than 80 mm. The dimensions of the false-ceiling hole cut out are indicated in the Chart. See instructions delivered with the fixtures.
Body	Corrosion resistant extruded aluminium body. Corrosion resistant die-cast aluminium end caps.
Painting	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Standard Colour	AL aluminium grey
Option colors	GR graphite satin finish



Dimensions

Total device width (mm)	90
Total device length (mm)	1230
Weight (kg)	6.75



Optical System

Diffuser	Tempered safety glass - 8 mm thickness, mechanical and thermal shock resistant.
Optical System	Optical system with PMMA lenses.
Beam	narrow
Emission	direct
Adjustable	No



Photometrics

Return DOWN LOR (%)100%Total return LOR (%)100%

Sources

MacAdam	Step 3
Output Flux	1865 lm RGBW
Source type	LED RGBW
System power	57W
Temperature Colour	RGBW

Electrical

Ballast type	DMX.
Frequency	50-60Hz
Lifetime	50.000h L80B50 (Ta=25°C)
Line input	Pre-wired and tested H07RN-F cable section 3x1,5mm ² and PUR cable section 1x2x0,25mm ² for DMX signal.
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No

Optional Accessories

Optical

**D49/4-HL**

NASTER honeycomb louver for Wall Grazing optic L=1230mm.