

SLIM D59 / D59 SLIM / SLIM/WB2 / D59/LWN-WB2-R-AL

Product Info




Item code	SLIM D59 / D59/LWN-WB2-R-AL
Category	Wall mounted
Environments	façades and architectural works, wellness, hallway, retail areas, places of worship
Mounting type	surface
Body	Corrosion resistant die-cast aluminium body.
Painting	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Standard Colour	AL aluminium grey
Option colors	GR graphite satin finish




Dimensions

Total device height (mm)	200
Total device width (mm)	56
Total device length (mm)	120





Optical System

Optical System	Safety tempered glass diffusers.
Beam	diffuse
Emission	double emission
Adjustable	No



Photometrics



h (m)	Ø (m)	$\gamma=0.0 \quad \alpha=\beta=104^\circ$		Emed (lx)
5.00	12.74			2
3.00	7.64			7
1.00	2.55			60
1.00	2.55			60
3.00	7.64			7
5.00	12.74			2
$\gamma=0.0 \quad \alpha=\beta=104^\circ$				

Sources

MacAdam	Step 3
Output Flux	840 lm
Source type	LED COB
System power	10W
Temperature Colour	4000K CRI>80

Electrical

Ballast type	ON-OFF.
Frequency	50-60Hz
Lifetime	50.000h L80B20 (Ta=25°C)
Line input	Complete with pre-wired and tested watertight H07RN-F cable.
Mounting ballast type	Integral
Voltage	220-240V
Separate ignition	No
Emergency 1E	No
Emergency 3E	No