

DLSB185 LED OPAL COVER - 95 MM



Part number	818712434001
Lampholder:	LED
Light Source:	LED
Wattage:	26 W
Finish:	WH-RAL9016 / White RAL9016 / Textured
Insulation class:	I
Degree of protection:	IP20
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor / COS Φ:	0.9
EEL:	A2
Optic:	Extra wide circle reflector
Optic Beam:	2 x 46°
Lightsource lumen output:	3410 lm
Luminaire lumen output:	2440 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire (°C):	10
Ta MAX luminaire (°C):	40




Description

Recessed, modular, round LED downlight for indoor, comprising:

- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
- Light-tight housing (prevents light diffusion in the suspended ceiling)
- Suitable for ceiling tile thickness from 1-25 mm
- Recessed frosted diffuser for optimal light distribution and high homogeneity
- White modular reflector, ABS injection-moulded with light-tight connection of LED board
- Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Built-in driver
- Protection class IP54 (for light emission surface for installation in closed ceilings)

Photometric data



Technical drawings

