

DLSB220 LED OPAL COVER - 95 MM



Part number	822720864003
Lampholder:	LED
Light Source:	LED
Wattage:	18 W
Finish:	WH-RAL9016 / White RAL9016 / Textured
Insulation class:	I
Degree of protection:	IP20
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
EEL:	A1
Optic:	EXTRA WIDE CIRCLE REFLECTOR
Optic Beam:	2x47°
Lightsource lumen output:	2750 lm
Luminaire lumen output:	2090 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°




Description

Recessed round LED downlight for indoors, consisting of:

- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
- Light-tight housing (prevents light diffusion in the suspended ceiling)
- Suitable for ceiling tile thickness from 1-25 mm
- Recessed frosted diffuser for optimal light distribution and high homogeneity
- White modular reflector, ABS injection-moulded with light-tight connection of LED board
- Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
- Colour rendering index Ra > 80
- Colour tolerance according to MacAdam \leq 3 SDCM
- Dimmable via TouchDIM®
- Complete with electric converter
- DALI dimmable
- Emergency 1h
- Protection class IP54 (for light emission surface for installation in closed ceilings)

Photometric data



Technical drawings

