

# DLSB220 LED OPAL COVER - 95 MM




<b>Part number</b>	822721733001
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	38 W
<b>Finish:</b>	WH-RAL9016 / White RAL9016 / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP20
<b>IK-J-xxIP:</b>	IK07 2J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor / COS Φ:</b>	0.9
<b>EEL:</b>	A2
<b>Optic:</b>	Extra wide circle reflector
<b>Optic Beam:</b>	2x47°
<b>Lightsource lumen output:</b>	4240 lm
<b>Luminaire lumen output:</b>	3380 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire (°C):</b>	10
<b>Ta MAX luminaire (°C):</b>	40



## Description

- Recessed, modular, round LED downlight for indoor, comprising:
- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
  - Light-tight housing (prevents light diffusion in the suspended ceiling)
  - Suitable for ceiling tile thickness from 1-25 mm
  - Recessed frosted diffuser for optimal light distribution and high homogeneity
  - White modular reflector, ABS injection-moulded with light-tight connection of LED board
  - Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
  - Colour tolerance according to MacAdam  $\leq 3$  SDCM
  - Built-in driver
  - Protection class IP54 (for light emission surface for installation in closed ceilings)

## Photometric data



## Technical drawings

