

DLSB220 LED OPAL COVER - 95 MM




Part number	822721764001
Lampholder:	LED
Light Source:	LED
Wattage:	38 W
Finish:	WH-RAL9016 / White RAL9016 / Textured
Insulation class:	I
Degree of protection:	IP20
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor / COS Φ:	0.9
EEL:	A1
Optic:	Extra wide circle reflector
Optic Beam:	2x47°
Lightsource lumen output:	4880 lm
Luminaire lumen output:	3690 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire (°C):	10
Ta MAX luminaire (°C):	40



Description

- Recessed, modular, round LED downlight for indoor, comprising:
- Multi-purpose die-cast aluminium housing combines all functions: heat-sinking, ceiling trim, ceiling brackets and gear tray connection
 - Light-tight housing (prevents light diffusion in the suspended ceiling)
 - Suitable for ceiling tile thickness from 1-25 mm
 - Recessed frosted diffuser for optimal light distribution and high homogeneity
 - White modular reflector, ABS injection-moulded with light-tight connection of LED board
 - Excellent heat dissipation through die-cast aluminium heat sink with FAST (Flexible Air Stream) Technology
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Dimmable via TouchDIM®
 - Built-in driver
 - DALI dimmable
 - Protection class IP54 (for light emission surface for installation in closed ceilings)

Photometric data



Technical drawings

