


FL ROUND+ 333 RE



Scan the QR-code for the latest information

- GR-RAL9006 / Grey RAL9006 / Textured
- BK-RAL9005 / Black RAL9005 / Textured
- WH-RAL9016 / White RAL9016 / Textured

Recessed round LED luminaire for indoor, comprising:

- Housing made from sheet steel and die-cast aluminium, powder-coated
 - Future-proof thanks to simple revisions (replaceable light engine and converter)
- The luminaire is available with different light engines:
- Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP)
 - Opal white diffuser for optimum light distribution and excellent uniformity (OP)
 - LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
 - Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
 - Integrated twist-in system for quick installation and easy maintenance
 - Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
 - Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
 - Depending on the version, glare-free light for office applications in accordance with DIN EN 12464-1 ($UGR < 19$ and $< 3000 \text{cd/m}^2 > 65^\circ$)
 - In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K (DALI DT8)
 - Direct light distribution
 - 2 power levels adjustable
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Through-wiring designed
 - Built-in driver




Public Utilities Company - Lehrte - Germany



FL ROUND+ 333 / 555 - 777 SM



FL ROUND+ 333 / 555 - 777 PL



FL ROUND+ 333 RE

FL ROUND+ 333 RE MP

IP20 - IK06 - 650 °C



LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIVEN 12664-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3123859	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3123849	✓
8 25		-	-	80	4000	1300 4000	1020 3040	■	3124791	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3124789	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3123863	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3123853	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1020 3040	■	3123857	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3123847	✓
8 25		-	-	80	4000	1300 4000	1020 3040	■	3124790	✓
8 25		-	-	80	3000	1260 3880	970 2890	■	3124788	✓
8 25		-	-	80	4000	1300 4000	1020 3040	□	3123861	✓
8 25		-	-	80	3000	1260 3880	970 2890	□	3123851	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	■	3123866	✓
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	■	3124792	✓
8 25		-	-	80	tw 2700-6500	1250 3900	960 2950	□	3123868	✓

FL ROUND+ 333 RE OP

IP20 - IK06 - 650 °C




LUMINAIRE WATTAGE (W)	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123860	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123850	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123856	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123846	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3123864	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3123854	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz										
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123858	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123848	✓
8 25		-	-	80	4000	1300 4000	1050 3180	■	3123855	✓
8 25		-	-	80	3000	1260 3880	1000 3020	■	3123845	✓
8 25		-	-	80	4000	1300 4000	1050 3180	□	3123862	✓
8 25		-	-	80	3000	1260 3880	1000 3020	□	3123852	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz										
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3123867	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	■	3123865	✓
8 25		-	-	80	tw 2700-6500	1250 3900	1010 3100	□	3123869	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
FL ROUND+ 333 RE			
External Casambi module	■	3122585	✓
Single wireless wall switch	□	3122586	✓
Double wireless wall switch	□	3122587	✓



3122585



3122586



3122587

