

FL ROUND 777 SM MP CORONA




Part number	8777661483410
Lampholder:	LED
Light Source:	LED
Wattage:	44 W
Finish:	WH-RAL9016 / White RAL9016 / Textured
Insulation class:	I
Degree of protection:	IP20
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
EEL:	A2
Optic:	Symmetric mainly direct lighting
Optic Beam:	2 x 49°
Lightsource lumen output:	6000 lm
Luminaire lumen output:	5130 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°



Description

- Surface-mounted round LED luminaire for indoor, comprising:
- Housing made from sheet steel and diecast aluminium, powder-coated
 - Micro-prismatic diffuser for efficient light diffusion, glare reduction and a high uniformity
 - LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the diffuser
 - Predominantly direct light distribution
 - VDU application suitable acc. to EN 12464-1
 - Colour rendering index Ra > 80
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Built-in driver

Photometric data



Technical drawings

