

GUELL 2.5



● GR-94 / Metallic grey / Textured

LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminum housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Anti-ageing silicone gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- The versions with A50/W optics comprise LED modules and reflectors specifically studied for settings that require highly asymmetrical light distribution.
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- 3000 K and 5000 K available upon request



GUELL 2.5
S/W




GUELL 2.5
A/W



GUELL 2.5
A50/W



GUELL 2.5
C/I



GUELL 2.5 S/W

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	158 W	I	80	4000		S/W	-	21619 lm	18062 lm	70	10	130000 h	●	306125

Power LED dimmable 1-10 V 220-240 V 50/60 Hz

LED	238 W	I	80	4000		S/W	-	33426 lm	29534 lm	70	10	130000 h	●	306201
LED	166 W	I	80	4000		S/W	-	22284 lm	20195 lm	70	10	130000 h	●	306199



GUELL 2.5 A/W

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	158 W	I	80	4000		A40/W	-	21619 lm	17511 lm	70	10	130000 h	●	306126

Power LED dimmable 1-10 V 220-240 V 50/60 Hz

LED	238 W	I	80	4000		A40/W	-	33426 lm	28464 lm	70	10	130000 h	●	306202
LED	166 W	I	80	4000		A40/W	-	22284 lm	19364 lm	70	10	130000 h	●	306200



GUELL 2.5 A50/W

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	156 W	I	80	4000		A50/W	-	24170 lm	18453 lm	70	10	130000 h	●	306204
LED	118 W	I	80	4000		A50/W	-	18127 lm	13862 lm	70	10	130000 h	●	306203

Power LED - dimmable DALI 220-240 V 50/60 Hz

LED	156 W	I	80	4000		A50/W	-	24170 lm	18453 lm	70	10	130000 h	●	306206
LED	118 W	I	80	4000		A50/W	-	18127 lm	13862 lm	70	10	130000 h	●	306205



GUELL 2.5 C/I

IK07 3J xx5

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	158 W	I	80	4000		C/I	-	21619 lm	17576 lm	70	10	130000 h	●	306207

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS ϕ $\geq 0,9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
LED	238 W	I	80	4000		C/I	-	33426 lm	27961 lm	70	10	130000 h	●	306210
LED	166 W	I	80	4000		C/I	-	22284 lm	18999 lm	70	10	130000 h	●	306209



OPTIONAL ACCESSORIES

DESCRIPTION	COLOR	PART NUMBER
GUELL 2.5 S/W (166 W - 238 W) Louvre GUELL 2.5 Symmetrical		310961
GUELL 2.5 A/W (166 W - 238 W) Louvre GUELL 2.5 Symmetrical		310962
GUELL 2.5 A/W - S/W (166 W - 238 W) GUELL 2.5 frosted glass	●	310964
GUELL 2.5 Cover GUELL 2.5	●	310963
Protective grid GUELL 2.5		310965
Wall mount support 1000 mm/39,37"	●	310982
Double pole top support GUELL 2.5	●	310967
Single pole top support GUELL 2.5	●	310966



310961 310962 310963 310964 310965



310982 310967 310966

