

GUELL 2.5 S/W




Part number	3102746
Lampholder:	LED
Light Source:	LED
Wattage:	158 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric wide reflector
Lightsource lumen output:	20806 lm
Luminaire lumen output:	16764 lm
L:	L70
B:	B10
Lifetime:	130000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°
ULR:	0%
IPEA* (Street Lighting):	A+
IPEA* (Area Lighting):	A4+
IPEA* (Cycle/Pedestrian Lighting):	A+
IPEA* (Green Areas):	A+
IPEA* (Historical Areas):	A6+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
 - Extra clear, tempered, flat glass diffuser
 - High-performance polished, oxidised, iridescence-free 99.99% pure aluminium reflector
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables $\varnothing 10$ - $\varnothing 14$ mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Integral surge protection device (SPD) against mains overvoltages up to 10 kV
 - For other colour temperatures and different colour rendering index consult factory
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

GUELL 2.5




310965
Protective grid GUELL 2.5



310982
Wall mount support 1000 mm
Metallic grey



310967
Double pole top support GUELL 2.5
Metallic grey



310966
Single pole top support GUELL 2.5
Metallic grey



14012294
Steel 'U' bolt clamp for Ø 60-80 mm
poles painted aluminium grey
Metallic grey