

GUELL 3 A/W




| | |
|---|----------------------------------|
| Part number | 06172294 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 238 W |
| Finish: | GR-94 / Metallic grey / Textured |
| Insulation class: | I |
| Degree of protection: | IP66 |
| IK-J-xxIP: | IK07 3J xx5 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COS ϕ \geq 0,9 |
| Optic: | Asymmetric wide reflector |
| Lightsource lumen output: | 33234 lm |
| Luminaire lumen output: | 25329 lm |
| L: | L70 |
| B: | B10 |
| Lifetime: | 130000 h |
| Ta MIN luminaire: | -30° |
| Ta MAX luminaire: | 40° |
| ULR: | 0% |
| IPEA* (Street Lighting): | A |
| IPEA* (Area Lighting): | A4+ |
| IPEA* (Cycle/Pedestrian Lighting): | A+ |
| IPEA* (Green Areas): | A+ |
| IPEA* (Historical Areas): | A5+ |
| Luminous Intensity Class: | G*6 |




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating ISO 9227
 - Flat extra clear tempered glass diffuser
 - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Integral surge protection device (SPD) against mains overvoltages up to 10 kV
 - Consult factory for other colour temperatures and colour rendering index
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES


GUELL 3



14452702
Protective grid




14453994
Wall mount support 1000 mm
Metallic grey



14453794
Single pole top support GUELL 3 for
poles \varnothing 60-76 mm/ \varnothing 2.36"-2.99"
Metallic grey




14453894
Double pole top support GUELL 3 for
poles \varnothing 60-76 mm/ \varnothing 2.36"-2.99"
Metallic grey



14461104
GUELL 3 strengthening bracket.
Suitable for one floodlight single
point fixing M10 screw in centre of the
bracket
Stainless steel

GUELL 3 A/W




14454520
Louvre GUELL 3 Asymmetrical A40/W



14452894
Louvre A40/W
Metallic grey

GUELL 3 A/W - S/W



14452994
Frosted glass GUELL 3
Metallic grey