

GUELL 2.5 A/W




Part number	3102744
Lampholder:	LED
Light Source:	LED
Wattage:	230 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	3000
Power factor / COS Φ:	0.9
Optic:	Asymmetric wide reflector
Lightsource lumen output:	34480 lm
Luminaire lumen output:	29368 lm
L:	L70
B:	B10
Lifetime:	130000 h
Ta MIN luminarie (°C):	-20
Ta MAX luminarie (°C):	30
ULR:	0%
IPEA* (Street Lighting):	A++
IPEA* (Area Lighting):	A6+
IPEA* (Cycle/Pedestrian Lighting):	A3+
IPEA* (Green Areas):	A3+
IPEA* (Historical Areas):	A7+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
 - Extra clear, tempered, flat glass diffuser
 - High-performance polished, oxidised, iridescence-free 99.99% pure aluminium reflector
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - Integral surge protection device (SPD) against mains overvoltages up to 10 kV
 - For other colour temperatures and different colour rendering index consult factory
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings




OPTIONAL ACCESSORIES

GUELL 2.5 A/W (166 W - 238 W)



310962
Louvre GUELL 2.5 Asymmetrical
A40/W


GUELL 2.5 A/W - S/W (166 W - 238 W)



310964
GUELL 2.5 frosted glass


Metallic grey

GUELL 2.5



310963
Cover GUELL 2.5 A40/W

Metallic grey



310965
Protective grid GUELL 2.5



310982
Wall mount support 1000 mm

Metallic grey



310967
Double pole top support GUELL 2.5

Metallic grey



310966
Single pole top support GUELL 2.5

Metallic grey



14012294
Steel 'U' bolt clamp for Ø 60-80 mm
poles painted aluminium grey

Metallic grey

