

GUELL 2.5 S/W




Part number	3115153
Lampholder:	LED
Light source:	LED
Wattage:	230 W
Finishing:	GR-94 / Metallic grey / Textured
Insulation class:	I
IP degree of protection:	IP66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor / COS Φ:	0.9
Optic:	Symmetric Wide optics
Lightsource lumen output (lm):	36440 lm
Luminaire lumen output (lm):	31072 lm
L:	L90
B:	B20
Lifetime:	65000 h
Min. ambient temperature (°C):	-20
Max. ambient temperature (°C):	30
IPEA* (road lighting):	A++
IPEA* (large areas, roundabouts):	A7+
IPEA* (cycle-pedestrian):	A4+
IPEA* (green areas):	A4+
IPEA* (historic city centers):	A8+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Extra clear, toughened, flat glass diffuser
 - High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel locking hardware
 - Fully integrated stainless steel aluminium spring clips
 - Powder-coated steel tiltable bracket
 - ON/OFF, DALI and 1-10V version available. Consult Factory
 - Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
 - High asymmetrical distributions low-glare optic options available (A50/W versions)
 - Openable and maintainable luminaire (future-proof)
 - Other colour temperatures (CCT) and colour rendering index (CRI) options available.
- Consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Design by GIORGIO LODI

Photometric data




Technical drawings



OPTIONAL ACCESSORIES


GUELL 2.5



310965
Protective grid GUELL 2.5



310982
Wall mount support 1000 mm
Metallic grey



310966
Single pole top support GUELL 2.5
Metallic grey




310967
Double pole top support GUELL 2.5
Metallic grey




14012294
Steel 'U' bolt clamp for Ø 60-80 mm
poles painted aluminium grey
Metallic grey

GUELL 2.5 S/W



310961
Louvre GUELL 2.5 Symmetrical

GUELL 2.5 S/W - GUELL 2.5 A/W



310964
GUELL 2.5 frosted glass
Metallic grey

