

## GUELL 2.5 S/W




<b>Part number</b>	3115155
<b>Lampholder:</b>	LED
<b>Light source:</b>	LED
<b>Wattage:</b>	230 W
<b>Finishing:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>IP degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	70
<b>Kelvin:</b>	5000
<b>Power factor / COS <math>\Phi</math>:</b>	0.9
<b>Optic:</b>	Symmetric Wide optics
<b>Lightsource lumen output (lm):</b>	38100 lm
<b>Luminaire lumen output (lm):</b>	35901 lm
<b>L:</b>	L90
<b>B:</b>	B20
<b>Lifetime:</b>	65000 h
<b>Min. ambient temperature (°C):</b>	-20
<b>Max. ambient temperature (°C):</b>	30
<b>IPEA* (historic city centers):</b>	A8+
<b>Luminous Intensity Class:</b>	G*6




### Description

- LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
  - Extra clear, toughened, flat glass diffuser
  - High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
  - Anti-ageing custom moulded silicone sealing gasket(s)
  - Cable gland M20x1.5 for cables  $\varnothing$  10-  $\varnothing$  14 mm
  - Stainless steel locking hardware
  - Fully integrated stainless steel aluminium spring clips
  - Powder-coated steel tiltable bracket
  - ON/OFF, DALI and 1-10V version available. Consult Factory
  - Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
  - High asymmetrical distributions low-glare optic options available (A50/W versions)
  - Openable and maintainable luminaire (future-proof)
  - Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Design by GIORGIO LODI

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### GUELL 2.5



310965  
Protective grid GUELL 2.5



310982  
Wall mount support 1000 mm  
Metallic grey



310966  
Single pole top support GUELL 2.5  
Metallic grey



310967  
Double pole top support GUELL 2.5  
Metallic grey




14012294  
Steel 'U' bolt clamp for Ø 60-80 mm  
poles painted aluminium grey  
Metallic grey

### GUELL 2.5 S/W



310961  
Louvre GUELL 2.5 Symmetrical

### GUELL 2.5 S/W - GUELL 2.5 A/W



310964  
GUELL 2.5 frosted glass  
Metallic grey

