

# GUELL 2.5




LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Anti-ageing silicone gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm

- The versions with A50/W optics comprise LED modules and reflectors specifically studied for settings that require highly asymmetrical light distribution.
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- All versions are available with 3000K LEDs on request
- Complete with supplementary device for protection against network surges of up to 10 kV



● GR-94 / Metallic grey / Textured




Please visit our web site  
[www.performanceinlighting.com](http://www.performanceinlighting.com)  
 for the latest updated versions available.

## GUELL 2.5 S/W

IK07 3J xx5


WATTAGE	CLASS	CRY	KELVIN	COS Ø >0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>													
158 W	I	-	80	4000	✓	S/W	-	21619 lm	18062 lm	70	10	130000 h	● 306125
158 W	I	-	80	3000	✓	S/W	-	20806 lm	16764 lm	70	10	130000 h	● 3102746
<b>Power LED dimmable 1-10 V 220-240 V 50/60 Hz</b>													
238 W	I	-	80	4000	✓	S/W	-	33426 lm	29534 lm	70	10	130000 h	● 306201
238 W	I	-	80	3000	✓	S/W	-	33099 lm	25987 lm	70	10	130000 h	● 3102747
166 W	I	-	80	4000	✓	S/W	-	22284 lm	20195 lm	70	10	130000 h	● 306199



## GUELL 2.5 A/W

IK07 3J xx5


WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\theta$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
158 W	I	-	80	4000	✓	A40/W	-	21619 lm	17511 lm	70	10	130000 h	●	<b>306126</b>
158 W	I	-	80	3000	✓	A40/W	-	20806 lm	16069 lm	70	10	130000 h	●	<b>3102743</b>
<b>Power LED dimmable 1-10 V 220-240 V 50/60 Hz</b>														
238 W	I	-	80	4000	✓	A40/W	-	33426 lm	28464 lm	70	10	130000 h	●	<b>306202</b>
238 W	I	-	80	3000	✓	A40/W	-	33099 lm	25517 lm	70	10	130000 h	●	<b>3102744</b>
166 W	I	-	80	4000	✓	A40/W	-	22284 lm	19364 lm	70	10	130000 h	●	<b>306200</b>



## GUELL 2.5 A50/W

IK07 3J xx5


WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\theta$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
156 W	I	✓	80	4000	✓	A50/W	-	24170 lm	18453 lm	70	10	130000 h	●	<b>306204</b>
118 W	I	-	80	4000	✓	A50/W	-	18127 lm	13862 lm	70	10	130000 h	●	<b>306203</b>
<b>Power LED - dimmable DALI 220-240 V 50/60 Hz</b>														
156 W	I	✓	80	4000	✓	A50/W	-	24170 lm	18453 lm	70	10	130000 h	●	<b>306206</b>
118 W	I	-	80	4000	✓	A50/W	-	18127 lm	13862 lm	70	10	130000 h	●	<b>306205</b>



## GUELL 2.5 C/I

IK07 3J xx5


WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\theta$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
158 W	I	-	80	4000	✓	C/I	-	21619 lm	17576 lm	70	10	130000 h	●	<b>306207</b>
<b>Power LED dimmable 1-10 V 220-240 V 50/60 Hz</b>														
238 W	I	-	80	4000	✓	C/I	-	33426 lm	27961 lm	70	10	130000 h	●	<b>306210</b>
166 W	I	-	80	4000	✓	C/I	-	22284 lm	18999 lm	70	10	130000 h	●	<b>306209</b>



## GUELL 2.5 C/W

IK07 3J xx5

WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\theta$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
158 W	I	-	80	4000	✓	C/W	-	21921 lm	16149 lm	70	10	130000 h	●	<b>3101130</b>
<b>Power LED dimmable 1-10 V 220-240 V 50/60 Hz</b>														
238 W	I	-	80	4000	✓	C/W	-	34876 lm	26106 lm	70	10	130000 h	●	<b>3101136</b>
166 W	I	-	80	4000	✓	C/W	-	23250 lm	17471 lm	70	10	130000 h	●	<b>3101134</b>



## OPTIONAL ACCESSORIES

DESCRIPTION	COLOR	PART NUMBER
<b>GUELL 2.5 S/W (166 W - 238 W)</b>		
Louvre GUELL 2.5 Symmetrical		<b>310961</b>
<b>GUELL 2.5 A/W (166 W - 238 W)</b>		
Louvre GUELL 2.5 Symmetrical		<b>310962</b>
<b>GUELL 2.5 A/W - S/W (166 W - 238 W)</b>		
GUELL 2.5 frosted glass	●	<b>310964</b>
<b>GUELL 2.5</b>		
Cover GUELL 2.5	●	<b>310963</b>
Protective grid GUELL 2.5		<b>310965</b>
Wall mount support 1000 mm	●	<b>310982</b>
Double pole top support GUELL 2.5	●	<b>310967</b>
Single pole top support GUELL 2.5	●	<b>310966</b>

