


GUELL 2

LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminum housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Anti-ageing silicone gasket
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- On request, versions with dimmable ballast available
- Passive infra-red motion sensor
- 3000 K and 5000 K available upon request



- GR-94 / Metallic grey / Textured



GUELL 2 C/IW

IK07 3J xx5 -

SOURCE	POWER	KELVIN	COLOUR/RAL	CRI	CLASS	OPTIC	NOMINAL LUMEN OUTPUT	LUMINAIRE LUMINOUS FLUX	LIFETIME	CODE
Power LED 220/240 V 50/60 Hz										
LED	78 W	4000 K	●	80	I	C/IW	11625 lm	8210 lm	L70 B10 150000 h	3101121
LED	105 W	4000 K	●	80	I	C/IW	14614 lm	10517 lm	L70 B10 150000 h	3101127

Accessories

DESCRIPTION	COLOUR/RAL	CODE
GUELL 2 C/IW		
Protective grid GUELL 2	-	14173502
Connection box IP 66	-	14174220
Wall support 500 mm/19.69" GUELL 1/2	●	14173394
Wall support 1000 mm/39.37" GUELL 1/2	●	14173494
Single pole top support GUELL 2	●	14174094
Double pole top support GUELL 2	●	14174194
Reinforcing bracket GUELL 2 in painted steel. Used to fasten the floodlight with a single screw in the centre of the bracket.	●	14460594
GUELL 2/C GR-94 frosted glass.	●	14476794

