

## GUELL 3 A/W




<b>Part number</b>	06170894
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	317 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Asymmetric wide reflector
<b>Lightsource lumen output:</b>	40936 lm
<b>Luminaire lumen output:</b>	30746 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	130000 h
<b>Ta MIN luminaire:</b>	-30°
<b>Ta MAX luminaire:</b>	30°




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
  - Extra clear, tempered, flat glass diffuser
  - High-performance polished, oxidised, iridescence-free 99.99% pure aluminium reflector
  - Anti-ageing silicone gasket
  - Cable gland M20x1.5 for cables  $\varnothing$  10-  $\varnothing$  14 mm
  - The versions with A50/W optics comprise LED modules and reflectors specifically studied for settings that require highly asymmetrical light distribution.
  - Stainless steel external screws
  - Fully integrated stainless steel aluminium spring clips
  - Powder coated steel bracket
  - Integral surge protection device (SPD) against mains overvoltages up to 10 kV
  - Openable and maintainable luminaire
  - For other colour temperatures and different colour rendering index consult factory
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES


### GUELL 3



14452702  
Protective grid




14453994  
Wall mount support 1000 mm  
Metallic grey



14453794  
Single pole top support GUELL 3 for  
poles  $\varnothing$  60-76 mm/ $\varnothing$  2.36"-2.99"  
Metallic grey




14453894  
Double pole top support GUELL 3 for  
poles  $\varnothing$  60-76 mm/ $\varnothing$  2.36"-2.99"  
Metallic grey



14461104  
GUELL 3 strengthening bracket.  
Suitable for one floodlight single  
point fixing M10 screw in centre of the  
bracket  
Stainless steel

### GUELL 3 A/W




14454520  
Louvre GUELL 3 Asymmetrical A40/W



14452894  
Louvre A40/W  
Metallic grey

### GUELL 3 A/W - S/W



14452994  
Frosted glass GUELL 3  
Metallic grey